

AMIX63



PRESENTATION

MIC/LINE PREAMPLIFIER

This compact mixer has been designed to mix several sound source.

FEATURES

MIC/LINE PREAMPLIFIER

This compact mixer has been designed to mix several sound source.

MAIN FEATURE

- Six balanced COMBO mic/line inputs
- Three unbalanced RCA stereo line inputs
- Line/phantom mic/mic input selectors
- Input signal LED indicators for each channel
- Adjustable MIC 1 priority function
- Independent gain controls for channels 1-9
- Two balanced XLR outputs (Left and Right)
- Balanced mono output
- Stereo REC output (Left and Right), RCA type
- Output signal level LED indicators (Left and Right)
- MASTER volume control
- Tone controls
- Emergency power connectors (24 V DC)
- 1U rack standard 19"

CODE: AMIX63

TECHNICAL SHEET

Ingressi: 6x MIC/LINE (con alimentazione Phantom 16~19 V DC) - 3 LINE

Sensibilità ingressi: INPUT CH1~CH6: 0 dBu - CH7~CH9: -10 dBu

Uscite di segnale: Stereo L R - Mono

Controlli:High: $\pm 15\text{dB}$ @ 12KHz - Mid: $\pm 12\text{dB}$ @ 2,5KHz - Low: $\pm 15\text{dB}$ @ 80Hz

Risposta in frequenza:20Hz-22KHz $\pm 3\text{dB}$

Distorsione Armonica Totale (THD): $\approx 0,03\%$ @ 1KHz

Rapporto Segnale/Rumore:INPUT CH1~CH6: $\approx 85\text{ dB}$ - CH7~CH9: $\approx 105\text{ dB}$

Alimentazione:230Vac 50/60Hz - 117Vac 50/60Hz (versione AMIX63V117)

Dimensioni (L x A x P):483x44x195 mm 1U Rack standard 19

Peso:2,9Kg

Connettori di ingresso:CH1~CH6: COMBO (XLR + JACK 6,3) - CH7~CH9: 2 x RCA

Connettori di uscita:XLR Male

Impedenza di ingresso:1,4 KOhm Micro - 10KOhm Line

Impedenza di uscita:1 KOhm REC OUT - 120 Ohm LINE OUT/MONO OUT

Guadagno:CH1~CH6: 0 dB to -50 dB
